

GEKA® quick couplings

Material:.....Brass CW617N
 Claw distance:.....Uniformly 40 mm. Combinations with each other and all GEKA® plus versions possible
 Operating pressure:.....**Max. 10 bar**
 Temperature range:.....Approx. -5 °C to +100 °C (depending on the quality of the sealing ring)
 Sealing:Standard with GEKA® high-performance shaped sealing rings form 200 NBR (80200C),
 temperature range from approx. -10 °C to +90 °C
 Options:Upon request GEKA® high-performance shaped sealing rings with the qualities NBR form 120
 (120AC), FKM (Fluororubber) according to DIN ISO 1629 form 200 (200V) as well as dirt strainers,
 available for self-assembly

GEKA® hose pieces

Grommet with raised end rib and hose protecting ribbed thread

Hose IW mm	10	13	16	19	25	32	38
Hose size	3/8"	1/2"	5/8"	3/4"	1"	1¼"	1½"
PU units	10	10	10	10	10	10	10
Covering box units	210	200	180	160	130	90	70
Catalogue no.	80100	80101	80102	80103	80104	80106	80107
EDV no.	08.0100	08.0101	08.0102	08.0103	08.0104	08.0106	08.0107



GEKA® threaded parts with female thread

Flat seal ring NBR at the threaded side

Female thread mm	11,89	15,39	19,17	24,66	30,93	39,59	45,48
Female thread	G 1/4"	G 3/8"	G 1/2"	G 3/4"	G 1"	G 1¼"	G 1½"
PU units	10	10	10	10	10	10	10
Covering box units	240	230	210	200	170	120	120
Catalogue no.	80108	80109	80110	80111	80113	80114	80116
EDV no.	08.1108	08.1109	08.1110	08.1111	08.1113	08.1114	08.1116



GEKA® threaded parts with male thread

Male thread mm	13,16	16,66	20,95	26,44	33,25	41,91	47,80
Male thread	G 1/4"	G 3/8"	G 1/2"	G 3/4"	G 1"	G 1¼"	G 1½"
PU units	10	10	10	10	10	10	10
Covering box units	240	230	220	230	190	170	140
Catalogue no.	80119	80109A	80110A	80111A	80113A	80114A	80116A
EDV no.	08.2119	08.2109	08.2110	08.2111	08.2113	08.2114	08.2116



GEKA® dummy coupling

With bore for fixing of little chains

PU units	10
Covering box units	230
Catalogue no.	80118
EDV no.	08.3118



1

