



FILCLAIR

Colour: transparent

Features:

- flexible PVC hose with polyester reinforcement, food quality
- temperature range : -15°C upto +60°C
- WP (working pressure) at 23°C
- BP (burstpressure) at 23°C

Application: various applications in industry, laboratories and for compressed air, alimentary liquids

ID mm	OD mm	tolerance mm	weight gr/mt	bending radius mm	WP bar	BP bar	length mt
4	8	+/- 0,2	49	40	10	30	50
4	10	+/- 0,2	86	40	15	50	50
6,3	11	+/- 0,2	82	50	10	30	50
6	12	+/- 0,2	110	55	15	50	25 - 50
8	13	+/- 0,5	105	65	10	30	50
8	14	+/- 0,5	130	60	15	50	25 - 50
9	15	+/- 0,5	141	65	15	50	25 - 50
10	15	+/- 0,5	131	85	10	30	50
10	16	+/- 0,5	155	75	15	50	25 - 50
12	18	+/- 0,5	170	105	10	30	50
12	19	+/- 0,5	216	80	15	50	25 - 50
12	21	+/- 0,5	297	85	15	50	50
13	19	+/- 0,5	192	80	10	30	50
13	20	+/- 0,5	225	90	15	50	25 - 50
15	23	+/- 0,5	308	100	15	50	25 - 50
16	22	+/- 0,5	222	155	10	30	50
19	26	+/- 0,8	302	195	10	30	50
19	27	+/- 0,8	363	125	15	50	25 - 50
20	28	+/- 0,8	372	130	15	50	25 - 50
25	33	+/- 0,8	432	235	10	30	50
25	34	+/- 0,8	524	150	15	50	25 - 50
25	36	+/- 0,8	622	160	15	50	50
30	40	+/- 0,8	670	180	12	38	25 - 50
32	42	+/- 0,8	716	185	12	38	25 - 50
38	48	+/- 1,0	865	220	10	32	25 - 50
40	50	+/- 1,0	885	240	8	24	25
45	57	+/- 1,0	1120	340	8	24	25
50	60	+/- 1,0	1072	390	8	24	25 - 50
50	64	+/- 1,0	1440	420	8	24	25 - 50