

Couplings „STORZ“ aluminium

Material:.....Aluminium, forged version
 Sealing:NBR black
 Please note:.....Industrial version, other dimensions and materials upon request



Fixed couplings „STORZ“ with male thread

Male thread mm	26.44	33.25	41.91	47.80	41.91	47.80
Male thread	G 3/4"	G 1"	G 1 1/4"	G 1 1/2"	G 1 1/4"	G 1 1/2"
Cleat distance mm	31	31	31	31	66	66
STORZ size	25-D	25-D	25-D	25-D	52-C	52-C
PU units	1	1	1	1	1	1
Catalogue no.	D502511	D502513	D502514	D502516	C505214	C505216
EDV no.	69.0032	69.0033	69.0034	69.0035	69.0036	69.0037

Male thread mm	59.61	75.18	75.18	87.88	113.03
Male thread	G 2"	G 2 1/2"	G 2 1/2"	G 3"	G 4"
Cleat distance mm	66	66	89	89	133
STORZ size	52-C	52-C	75-B	75-B	110-A
PU units	1	1	1	1	1
Catalogue no.	C505219	C505225	B507525	B507530	A501004
EDV no.	69.0038	69.0039	69.0040	69.0041	69.0042



Cleats „STORZ“ with female thread socket, rotatable

Female thread mm	57.29	72.86	85.56	110.71
Female thread	G 2"	G 2 1/2"	G 3"	G 4"
Cleat distance mm	66	89	89	133
STORZ size	52-C	75-B	75-B	110-A
PU units	1	1	1	1
Catalogue no.	C605219	B607525	B607530	A601004
EDV no.	69.0043	69.0044	69.0045	69.0046



Cleats „STORZ“ with male thread socket, rotatable

Male thread mm	59.61	75.18	87.88	113.03
Male thread	G 2"	G 2 1/2"	G 3"	G 4"
Cleat distance mm	66	89	89	133
STORZ size	52-C	75-B	75-B	110-A
PU units	1	1	1	1
Catalogue no.	C705219	B707525	B707530	A701004
EDV no.	69.0047	69.0048	69.0049	69.0050



Blind couplings „STORZ“ with chain

Cleat distance mm	31	66	89	133	148	160
STORZ size	25-D	52-C	75-B	110-A	125	160
PU units	1	1	1	1	1	1
Catalogue no.	D802818	C805218	B807518	A801008	A801258	A801608
EDV no.	69.0051	69.0052	69.0053	69.0054	69.0055	69.0056



Transition pieces „STORZ“

STORZ size 1	52-C	75-B	110-A	150
STORZ size 2	25-D	52-C	75-B	110-A
PU units	1	1	1	1
Catalogue no.	CD2552	BC7552	AB11075	A150110
EDV no.	69.0057	69.0058	69.0059	69.0060